



Discription


The HESDNC712B1EL-B protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events. Excellent clamping capability, low leakage, low capacitance, and fast response time provide best in class protection on designs that are exposed to ESD. It gives designer the flexibility to protect one bi-directional line in applications where arrays are not practical.



SOD-323

Features

- Protects two +12V to -7V lines
- Low clamping voltage: $V_{CL}=19V @ I_{PP}=18A(P1-P2)$,
 $V_{CL}=12V @ I_{PP}=18A(P2-P1)$,
- Ultra low leakage current: $I_{RM} < 10 \text{ nA}$
- IEC 61000-4-2(ESD): $\pm 30kV$ (Air), $\pm 30kV$ (Contact)
- IEC 61000-4-5 (surge): $I_{PPM}=18 \text{ A}$



Circuit Diagram

Application information

- RS-485 transceivers with extended common mode range
- Automatic Teller Machines
- Lighting Control-DALI
- Communication Equipments
- HFC systems
- Networks

Ordering Information

Product ID	Pack	Qty(PCS)
HESDNC712B1EL-B	SOD-323	3000

Absolute Ratings($T_{amb} = 25^{\circ}C$)


Parameter	Symbol	Value	Unit
Peak Pulse Power ($t_p = 8/20\mu S$)	P_{PK}	360/252	W
Peak Pulse Current($t_p = 8/20\mu S$)	I_{PP}	18/18	A
ESD voltage IEC 61000-4-2 (air discharge)	V_{ESD}	30	KV
ESD voltage IEC 61000-4-2 (contact discharge)	V_{ESD}	30	KV
Storage Temperature Range	T_{stg}	-55 to +150	$^{\circ}C$
Operating Temperature Range	T_{OP}	-40 to +85	$^{\circ}C$



Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.


Parameter	Symbol	Min	Typ	Max	Unit	Condition
Reverse Working Voltage	V_{RWM}	--	--	12	V	Pin1 To Pin2
		--	--	7	V	Pin2 To Pin1
Breakdown Voltage	V_{BR}	13	14.5	17.0	V	Pin1 To Pin2, $I_T=1mA$
		7.5	8.5	9.5	V	Pin2 To Pin1, $I_T=1mA$
Leakage Current I_{Leak}	I_R	--	--	50	nA	Pin1 To Pin2, $V_R=12V$
		--	--	50	nA	Pin2 To Pin1, $V_R=7V$
Clamping Voltage	V_C	--	19	20	V	Pin1 To Pin2, $I_{PP}=18A, T_p=8/20\mu s$
Clamping Voltage	V_C	--	12	14	V	Pin2 To Pin1, $I_{PP}=18A, T_p=8/20\mu s$
Junction Capacitance	C_J	--	30	32	pF	$V_R=0V, f=1MHz$

Symbol	Parameters
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}







Typical Characteristics




Time(nS)
IEC61000-4-2 Pulse Waveform




T-Time(μS)
IEC61000-4-5 8X20μs Pulse Waveform




Clamping Voltage vs. Peak Pulse Current (P1-P2 7V)




Clamping Voltage vs. Peak Pulse Current (P2-P1 12V)




Peak Pulse Power vs. Pulse Time (P1-P2 7V)



Junction Capacitance vs. Reverse Voltage(P2-P1 12V)




Voltage vs Current (P2-P1)




Clamping Voltage vs. Peak Pulse Current

OUTLINE AND DIMENSIONS



SYMBOL	DIMENSIONS	
	MIN	MAX
A	0.25	0.40
B	1.20	1.40
C	2.35	2.75
H	1.50	1.80
J	0.01	0.15
K	0.75	1.05
L	0.20	0.40
M	0.08	0.25
α	0°	8°

SOLDERING FOOTPRINT



SYMBOL	DIMENSIONS
A	3.20
B	0.80
C	0.80



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.