



Description

The HLM3063S1 series devices are optocouplers composed of a GaAs infrared light emitting diode and a single-crystal silicon chip random phase photoelectric bidirectional thyristor.

Features

- Peak breakdown voltage
- ELM3053(TA): Min.600V
- 4pin non zero-cross optoisolators triac driver outp
- High input-output isolation voltage(Viso = 3,750Vrms)
- Operating Temperature: -40℃~110℃
- RoHS


Applications

- Lighting Control
- AC Motor Starter
- Static power switc
- Temperature Controls



PIN 1

SOP-4



Pin Configuration

- 1 Anode
- 2 Cathode
- 3 GND
- 4 VCC

Maximum Rating

Parameter		Symbol	Values	Unit
Input	Forward Current	I_F	50	mA
	Reverse Voltage	V_R	6	V
	Power Dissipation	P	100	mW
	Junction Temperature	T_J	125	°C
Output	Off-State Output Terminal Voltage	V_{DRM}	600	V
	On state RMS current	$I_{T(RMS)}$	100	mA(RMS)
	Peak Repetitive Surge Current (PW=1ms,120μpps)	I_{TSM}	1	A
	Junction Temperature	T_J	125	°C
	Collector Power Dissipation	P_C	300	mW
Operating temperature range		T_{op}	- 40 ~ 110	°C
Storage temperature range		T_{stg}	- 55 ~ 125	°C
Total Power consumption		$P_{(W)}$	330	mW
Isolation Voltage ⁽¹⁾		V_{ISO}	3750	Vrms
Soldering Temperature ⁽²⁾		T_{SOL}	260	°C

Notes:

(1). AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 are shorted together, and pins 3, 4 are shorted together.

(2).For 10 seconds



Electronic Optical Characteristics
(TA = 25°C)

Parameter		Symbol	Min.	Typ.	Max.	Unit	Conditon
Input	Forward Voltage	V_F	-	1.2	1.6	V	$I_F=10\text{mA}$
	Reverse Current	I_R	-	-	5	μA	$V_R=6\text{V}$
Output	Peak Blocking Current, Either Directiot ⁽¹⁾	I_{DRM}	-	-	100	nA	$V_{\text{DRM}} = \text{Rated VDRM}$
	Peak On-State Voltage, Either Dire	V_{TM}	-	-	2.5	V	$I_{\text{TM}}=100\text{mA}$ Peak
	Critical rate of Rise of Off-State Voltage ⁽²⁾	dv/dt	1000	-	-	V/ μs	$V_{\text{in}}=240\text{Vrms}$
Transfer Charact eristics	Led Trigger Current, Current Required to Latch Output, Either Direction	I_{FT}	-	-	5	mA	Main Terminal Voltage = 3V
	Holding Current, Either Direction	I_H	0.5	1.0	5.0	mA	
	Turn-On Time	T_{on}	-	-	100	μs	$V_D=6\text{V}$ $R_L=100\ \Omega$ $I_F=20\text{mA}$

(1)Test voltage must be applied within dv/dt rating.

(2)This is static dv/dt . Commutating dv/dt is a function of the load-driving thyristor(s) only.



Characteristics Curves

Fig.1 Forward current vs.Ambient temperature




Fig.2 On-state current vs.Ambient temperature




Fig.3 Minimum Trigger Current vs.Ambient temperature




Fig.4 Forward current vs Forward Voltage




Fig.5 On-state voltage vs . Ambient temperature




Fig.6 Holding current vs Ambient temperature






Fig.7 Repetitive peak off-state current vs Temperature




Fig.8 On-state current vs On-state voltage




Fig.9 Basic Operation Circuit Medium/High Power Triac Drive Circuit






Fig10.Static dv/dt Test Circuit & Waveform






Outline Dimension



Unit: mm

Tolerance: ± 0.1 mm

Recommended solder pad Design



Unit: mm

Tolerance: ± 0.1 mm




Temperature Profile Of Soldering

1. IR Reflow soldering

(JEDEC-STD-020D compliant)

Profile item	Conditon
Preheat -Temperature Min (TSmin) -Temperature Max (TSmax) -Time (min to max) (ts)	150°C 200°C 90±30 sec
Soldering zone -Temperature (TL) -Time (tL)	217°C 60-150 sec
Peak Temperature (TP) -Time (TP-5°C to TP) (ts)	260°C 30sec
Ramp-up rate	3°C / sec max
Ramp-down rate	3~6°C/ sec



Notes:

One time soldering reflow is recommended within the condition of temperature and time profile shown below.
Do not solder more than three times.



2. Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition.

Temperature: $260 \pm 0/-5^{\circ}\text{C}$.

Time: 10 sec.

Preheat temperature: 25 to 140°C .

Preheat time: 30 to 80 sec.



3. Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature: $380 \pm 0/-5^{\circ}\text{C}$

Time: 3 sec max.



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.