
2N3904S-RTK/PS


NPN Plastic-Encapsulate Transistors

Features

- Collector Current: I_C=0.2A
- Power Dissipation of 200mW



SOT-23



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
2N3904S-RTK/PS	SOT-23	1AM	3000


Maximum Ratings (Ta=25℃ unless otherwise noted)


Parameter	Symbol	Limit	Unit
Collector-Base Voltage	V_{CBO}	60	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Base Voltage	V_{EBO}	6	V
Collector Current	I_C	200	mA
Collector Power Dissipation	P_C	200	mW
Thermal Resistance From Junction To Ambient	$R_{\Theta JA}$	625	℃/W
Junction Temperature	T_j	150	℃
Storage Temperature	T_{stg}	-55～+150	℃


Electrical Characteristics (Ta=25℃unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=10μA, I_E=0	60		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=1mA, I_B=0	40		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=10μA, I_C=0	6		V
Collector cut-off current	I_{CEX}	V_{CE}=30V, $V_{EB(off)}$=3V		50	nA
Collector cut-off current	I_{CBO}	V_{CB}= 60V, I_E=0		100	nA
Emitter cut-off current	I_{EBO}	V_{EB}=5V, I_C=0		100	nA
DC current gain	$h_{FE(1)}$	V_{CE}=1V, I_C=10mA	100	300	
	$h_{FE(2)}$	V_{CE}=1V, I_C=50mA	60		
	$h_{FE(3)}$	V_{CE}=1V, I_C=100mA	30		
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=50mA, I_B=5mA		0.3	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=50mA, I_B=5mA		0.95	V
Transition frequency	f_T	V_{CE}=20V,I_C=10mA, f=100MHz	300		MHz
Delay time	t_d	V_{CC}=3V, $V_{BE(off)}$=-0.5V I_C=10mA, I_{B1}=1mA		35	ns
Rise time	t_r	V_{CC}=3V, $V_{BE(off)}$=-0.5V I_C=10mA, I_{B1}=1mA		35	ns
Storage time	t_s	V_{CC}=3V, I_C=10mA, I_{B1}= I_{B2}=1mA		200	ns
Fall time	t_f	V_{CC}=3V, I_C=10mA, I_{B1}= I_{B2}=1mA		50	ns


Typical Characteristics









V_{CEsat} — I_C
COLLECTOR-EMITTER SATURATION VOLTAGE V_{CEsat} (mV)
600
300
100
30
10
T_a=100℃
T_a=25℃
β=10
1
3
10
30
100
200
COLLECTOR CURRENT I_C (mA)


V_{BEsat} — I_C
BASE-EMITTER SATURATION VOLTAGE V_{BEsat} (V)
1.2
0.8
0.4
0.0
T_a=25℃
T_a=100℃
β=10
1
3
10
30
100
300
COLLECTOR CURRENT I_C (mA)



I_C — V_{BE}
COMMON EMITTER
V_{CE}=1V
COLLECTOR CURRENT I_C (mA)
100
30
10
3
1
0.3
0.1
T_a=100℃
T_a=25℃
0.2
0.4
0.6
0.8
1.0
1.2
BASE-EMITTER VOLTAGE V_{BE} (V)


C_{ob} / C_{ib} — V_{CB} / V_{EB}
f=1MHz
I_E=0/I_C=0
T_a=25℃
CAPACITANCE C (pF)
9
3
1
C_{ib}
C_{ob}
0.1
0.3
1
3
10
20
REVERSE VOLTAGE V (V)


f_T — I_C
V_{CE}=20V
T_a=25℃
TRANSITION FREQUENCY f_T (MHz)
300
200
100
1
3
10
30
60
COLLECTOR CURRENT I_C (mA)



P_C — T_a
COLLECTOR POWER DISSIPATION P_C (mW)
250
200
150
100
50
0
0
25
50
75
100
125
150
AMBIENT TEMPERATURE T_a (℃)

SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.