



Features

- Total power dissipation: Max. 2 W.
- Wide zener reverse voltage range 3.3V to 330V.
- Small plastic package suitable for surface mounted design.



SMA
(DO-214AC)



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
SMA2EZ3.3-SMA2EZ100	SMA (DO-214AC)	XX	3000

XX=Device code, see table on page2 the marking code.

The marking bar indicates the cathode.

Absolute Maximum Ratings(Ta=25°C)

Characteristic	Symbol	Value	Unit
Forward voltage @I _F =200mA	V _F	1.2	V
Power Dissipation	P _D	2	W
Thermal Resistance, Junction to Ambient Air	R _{θJA}	556	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{stg}	-55 ~ +150	°C

Notes: Device mounted on ceramic PCB;5.0mm×7.0mm with pad areas 35 mm²



Electrical Characteristics (Ta=25℃ unless otherwise specified)

Part Number	Marking Code	Zener Vol Tage Range	Test Current		Reverse Current		Dynamic Resistance		Surge Current (1)
		V _Z at I _{ZT1}	I _{ZT1}	I _{ZT2}	I _R at V _R		Z _Z at I _{ZT1}	Z _{ZK} at I _{ZT2}	I _{RM}
		V	mA		μA	V	Ω		mA _{pk}
		NOM.			MAX.		MAX.	MAX.	MAX.
SMA2EZ3.3D5	3P3	3.3	76	1	100	1	10	400	1380
SMA2EZ3.6D5	3P6	3.6	69	1	100	1	10	400	1260
SMA2EZ3.9D5	3P9	3.9	64	1	50	1	9	400	1190
SMA2EZ4.3D5	4P3	4.3	58	1	10	1	9	400	1070
SMA2EZ4.7D5	4P7	4.7	53	1	10	1	8	500	970
SMA2EZ5.1D5	5P1	5.1	49	1	10	1	7	550	890
SMA2EZ5.6D5	5P6	5.6	45	1	10	2	5	600	810
SMA2EZ6.2D5	6P2	6.2	41	1	10	3	2	700	730
SMA2EZ6.8D5	6P8	6.8	37	1	10	4	3.5	700	660
SMA2EZ7.5D5	7P5	7.5	34	0.5	10	5	4	700	605
SMA2EZ8.2D5	8P2	8.2	31	0.5	10	6	4.5	700	550
SMA2EZ9.1D5	9P1	9.1	28	0.5	10	7	5	700	500
SMA2EZ10D5	10	10	25	0.25	10	7.6	7	700	454
SMA2EZ11D5	11	11	23	0.25	5	8.4	8	700	414
SMA2EZ12D5	12	12	21	0.25	5	9.1	9	700	380
SMA2EZ13D5	13	13	19	0.25	5	9.9	10	700	344
SMA2EZ15D5	15	15	17	0.25	5	11.4	14	700	305
SMA2EZ16D5	16	16	15.5	0.25	5	12.2	16	700	285
SMA2EZ18D5	18	18	14	0.25	5	13.7	20	750	250
SMA2EZ20D5	20	20	12.5	0.25	5	15.2	22	750	225
SMA2EZ22D5	22	22	11.5	0.25	5	16.7	23	750	205
SMA2EZ24D5	24	24	10.5	0.25	5	18.2	25	750	190
SMA2EZ27D5	27	27	9.5	0.25	5	20.6	35	750	170
SMA2EZ30D5	30	30	8.5	0.25	5	22.8	40	1000	150
SMA2EZ33D5	33	33	7.5	0.25	5	25.1	45	1000	135
SMA2EZ36D5	36	36	7	0.25	5	27.4	50	1000	125
SMA2EZ39D5	39	39	6.5	0.25	5	29.7	60	1000	115
SMA2EZ43D5	43	43	6	0.25	5	32.7	70	1500	110
SMA2EZ47D5	47	47	5.5	0.25	5	35.8	80	1500	95
SMA2EZ51D5	51	51	5	0.25	5	38.8	95	1500	90
SMA2EZ56D5	56	56	4.5	0.25	5	42.6	110	2000	80
SMA2EZ62D5	62	62	4	0.25	5	47.1	125	2000	70
SMA2EZ68D5	68	68	3.7	0.25	5	51.7	150	2000	65
SMA2EZ75D5	75	75	3.3	0.25	5	56	175	2000	60
SMA2EZ82D5	82	82	3	0.25	5	62.2	200	3000	55
SMA2EZ91D5	91	91	2.8	0.25	5	69.2	250	3000	50
SMA2EZ100D5	100	100	2.5	0.25	5	76	350	3000	45

Note

(1) Surge current is a non-repetitive, 8.3 ms pulse width square wave or equivalent sine-wave superimposed on I_{ZT} per JEDEC® method



Typical Characteristics




Fig. 1 - Maximum Continuous Power Dissipation




Fig. 4 - Typical Instantaneous Forward Characteristics for SMA2EZ4763




Fig. 2 - Typical Zener Impedance




Fig. 5 - Typical Reverse Characteristics





Fig. 3 - Typical Temperature Coefficients



Package Outline Dimensions

SMA(DO-214AC)



Dimensions in inches and (millimeters)



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.